

CONVECTOR PAN SEALANT

RUBBERIZED FLEXIBLE COATING

CONVECTOR PAN SEALANT provides a durable, flexible, rubberized film which is impervious to water. **CONVECTOR PAN SEALANT** forms a tough rubberized coating that seals out rust and corrosion on air conditioning and refrigerator condensation drain pans while reducing unwanted vibration and sound.



CONVECTOR PAN SEALANT

Rubberized Flexible Coating

NON-CHLORINATED

SEALS OUT RUST & CORROSION

UNAFFECTED BY WEATHER

FOR USE BY:

Apartment Buildings
Construction Co.
Manuf. Facilities
Hotels/Motels
HVAC Maint.
Machine Shops
Maint. Operations
Office Buildings

FOR USE ON:

Metal Walls
Metal Sinks
Plastic Piping
A/C Pans
Refrigeration Pans
Tree-Pruning Wounds
Ducts
Electrical Junction Boxes.

FEATURE-BENEFIT:

Non-Chlorinated
Reduces Squeaks and Vibration.
Flexible and Tough.
Seals Out Rust and Corrosion.
Water-Resist

CONVECTOR PAN SEALANT

RUBBERIZED FLEXIBLE COATING

DIRECTIONS:

SHAKE WELL UNTIL BALL RATTLES FREE

Apply to a clean, dry surface. Do not use if temperature of can is below 60°F. Spray surface with short, even strokes from a distance of 12 to 14 inches. Several thin coats are better than one heavy coat.

TECHNICAL DATA:

Appearance and Odor: Thick, Black Viscous Liquid, Solvent
Flash Point of Concentrate: Odor
Flammability: 60°F
Extinguishing Media: Extremely Flammable Spray
Propellant: Foam, CO, Dry Media
Spray Pattern: Liquefied Petroleum Gas
Circular

CONTACT INFORMATION

OFFICE:
1-888-6PURITY (678-7489)
FAX
1-877-9PURITY (978-7489)
ADDRESS:
114 SOUTHFIELD PKWY
SUITE 120
FOREST PARK GA. 30297
www.puritychemicals.com

MATERIAL SAFETY DATA SHEET
COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)



SECTION I · PRODUCT IDENTIFICATION

Product Name: Convector Pan Sealant
Product Number: 641
Product Type: AEROSOL
Distributor's Name: Purity Chemicals
Distributor's Address: 114 Southfield Pkwy Suite 120
Forest Park, GA 30297
D.O.T. Hazard Class: CONSUMER COMMODITY · ORM-D

Formula: Proprietary
Date Prepared: 03/09/05
Emergency Phone: (800) 255-3924
Distributor's Phone: (404) 363-0797

HMS Rating (Based on Aerosol Conc.):
0-Minimal 1- Slight 2- Moderate
3- Serious 4- Extreme
HEALTH: 2 FIRE: 3 REACTIVITY: 0
Personal Protection: C

SECTION II · INGREDIENTS

CHEMICAL NAME	CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TWA/TLV
Toluene	108-88-3	20-30	YES	NO	NO	100 ppm	100 ppm
Aliphatic Petroleum Distillate	8052-41-3	10-20	NO	NO	NO	500 ppm	100 ppm
Aliphatic Petroleum Solvent	64742-89-8	01-10	NO	NO	NO	300 ppm	300ppm
Calcium Carbonate	1317-65-3	01-10	NO	NO	NO	15 mg/m ³ (dust)	10 mg/m ³ (dust)
Carbon Black	1333-86-4	01-05	NO	NO	IARC 2B	3.5 mg/m ³ (dust)	N/E
Liquified Petroleum Gas	68476-85-7	20-40	NO	NO	NO	1000 ppm	1000 ppm

SECTION III · PHYSICAL DATA

Data Below Based On Aerosol Concentrate Only:

Boiling Point: >300° F

pH: N/A

Solubility In Water: Not Soluble

Appearance/Odor: Black Viscous Liquid, Solvent Odor

Data Below Based On Total Contents:

Vapor Pressure of can (psig @70°F): 45

Total VOC %: ~ 70.2%

Vapor Density(Air=1): >1

Specific Gravity (H₂O=1)@75°F: 0.940

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (of Concentrate Only): 60°F (T.O.C.)

Flammability (as per USA Flame Projection Test): Extremely-Flammable Spray

Extinguishing Media: Foam, CO₂, Dry Media

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.

SECTION V · REACTIVITY DATA

Stability: Material Stable.

Hazardous Polymerization: Will not Occur.

Incompatibility: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxides.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120° F.

NFPA Code 30B Rating: Level 3 Aerosol.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause slight irritation but does not injure eye tissue.

Skin: Frequent or prolonged contact may cause irritation.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.

Ventilation: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

Protective Gloves: None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.

Eye Protection: None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT EST

ABLISHED · N/D=NOT DETERMINED

· <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.