

DRY LUBE

DRY LUBRICANT AND RELEASE AGENT

DRY LUBE is a PTFE lubricant that is specially made for lubricating items that require a clean dry substance to reduce friction at medium to low load resistance. **DRY LUBE** lubricates virtually any surface and acts as a release agent. Since **DRY LUBE** is non-oily and chemically inert, it will not attract dust, dirt, lint, or atmospheric particles. It prevents sticking, dragging, and hang-ups while withstanding temperatures up to 500° F.

FOR USE BY:

Body Shops
Hospitals
Hotels/Motels
Install Operations Re-
pair Operations
Machine Shops
Mechanics
Municipal Buildings
Nursing Homes
Office Buildings
Schools

FOR USE ON:

Bearings
Chain Drives
Equip. Linkages
Gear Drives
Hinges
Locks
Pulleys
Slide Mechanisms
Sliding Doors & Windows

FEATURE-BENEFIT:


Dry Lubrication
No Silicones
No Petroleum Oil
Repels Dust & Dirt
Non-Oily
Non-Staining
Reduces Friction
Molding Release Agent
Safe on Metal, Plastic, and Wood Surfaces

DIRECTIONS:

Shake well before using. Clean surface to be treated. Hold the can 6 inches away from yourself and spray a fine thin film on surface. Reapply as needed.

TECHNICAL DATA:

Appearance and Odor: Brownish Liquid, Solvent Odor
Flash Point of Concentrate: 200° F-T.O.C.
Flammability: Non-Flammable Spray
Specific Gravity: 0.833
Propellant: Carbon Dioxide
Spray Pattern: Circular Spray
NFPA Fire Rating: Level 3 Aerosol



DRY LUBE DRY LUBRICANT AND RELEASE AGENT

CONTACT INFORMATION

OFFICE:
1-888-6PURITY (678-7489)
FAX
1-877-9PURITY (978-7489)
ADDRESS:
114 SOUTHFIELD PKWY
SUITE 120
FOREST PARK GA. 30297
www.puritychemicals.com



MATERIAL SAFETY DATA SHEET

SECTION 1 IDENTIFICATION

Product Name: **Dry Lube**
Distributor's Name: Purity Chemicals, Inc.
Distributor's Address: 114 Southfield Pkwy., Suite 120, Forest Park, GA 30297
Distributor's Phone Number (404) 363-0767
Emergency Phone Number: 1-800-535-5053
Proper Shipping Name: Consumer Commodity, ORM-D
Effective Date: 10-15-01

SECTION 2 IDENTITY INFORMATION AND HAZARDOUS INGREDIENTS

Chemical Name: CAS No.: TLV:
Aliphatic Petroleum Distillates 64742-89-8 Not established
Propane 74-98-6 2500ppm Isobutane 75-28-5 Not established n-Butane 106-97-8 800ppm

SECTION 3 PHYSICAL DATA

Boiling Point: <0 to 2120 F Specific Gravity(H₂O=1): 0.80 + 0.05
Solubility in Water: Nil Evaporation Rate: Slower than Ether
Vapor Density (Air=1): Heavier than air pH: NA

SECTION 4 FIRE AND EXPLOSION HAZARD DATA

Flash Point: 140OF
Flash Point (Propellant): <0OF
Flammable Limits (Propellant): LEL: 1.8 UEL: 9.5 Extinguishing Media: Use water fog, dry chemical or carbon dioxide. Special Fire Fighting Procedures: Aerosol cans may rupture when heated. Unusual Fire and Explosion Hazards: Heated cans may burst.

SECTION 5 REACTIVITY DATA

Stability: Unstable _____
Stable X
Incompatibility (Materials to Avoid): None known. Conditions to Avoid: High temperatures. Hazardous Decomposition or Byproducts: In fire, will decompose to carbon dioxide, carbon monoxide, hydrogen fluoride. Hazardous Polymerization: Will not occur

SECTION 6 STORAGE AND HANDLING INFORMATION

Precautions to be Taken in Handling and Storing: When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator. STORE AT TEMPERATURES BELOW 120°F KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME KEEP AWAY FROM CHILDREN FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY FOR USE BY TRAINED PERSONNEL ONLY KEEP CONTAINER CLOSED DURING STORAGE

Effects of Overexposure:

SKIN: Skin irritant. Will cause defatting of skin. Effects are reversible. **EYES:** Eye irritant. Will cause redness and burning sensation. **INHALATION:** Effects of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death. **INGESTION:** Aspiration hazard if swallowed. **First Aid Procedures:** **SKIN:** Immediately flush exposed area with water for at least 15 minutes. If irritation persists, get medical attention. Remove contaminated clothing and launder before reuse. **EYES:** Immediately flush with large quantities of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Seek medical attention. **INHALATION:** Remove person to fresh air. If irritation persists, give oxygen, get medical attention. **INGESTION:** DO NOT induce vomiting. Seek medical attention immediately. **Note:** Never give anything by mouth to an unconscious or convulsing victim. Keep person warm and quiet.

SECTION 8 SPECIAL PROTECTION INFORMATION

Respiratory Protection: Self-contained breathing apparatus if above TLV limit.
Ventilation: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.
Protective Gloves: None required if spraying. Eye Protection: As with all cleaners, PURITY supports employee safety as priority #1. Therefore, we recommend the use of safety glasses or chemical splash goggles. Other Protective Equipment: Long sleeves and long pants. Work Hygienic Practices: Do not smoke while using. Wash hands after use.

SECTION 9 SPILL OR LEAK PROCEDURE

Steps To Be Taken In Case Material Is Released or Spilled:
Use absorbent sweeping compound to soak up material. Put into container. Dispose as hazardous waste. Waste Disposal Method: Dispose as hazardous waste in accordance with EPA RCRA.

SECTION 10 REGULATORY INFORMATION

SARA Title III, Section 313 Components:
Aliphatic Petroleum Distillates contain a maximum of 4% cyclohexane (110-82-7) which is subject to the reporting requirements of SARA Title III, Section 313.

This information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition. We make no warranties, express or implied, and assume no liability in connection with any use of this information. 496205