

# GOOD GRIP

## SLIP RESISTANT COATING

**GOOD GRIP** is designed to improve traction on most surfaces. **GOOD GRIP** is an aerosol manufactured with a special plastic bead suspended in an epoxy resin system. **GOOD GRIP** epoxy resin provides a tough, durable finish, which also makes **GOOD GRIP** very good for oil and gasoline resistance. And with it's special valve and spray head, clogging is impeded. **GOOD GRIP** also comes in a variety of colors including black, gray, white, yellow, and clear.



FOR USE BY:	FOR USE ON:	FEATURE-BENEFIT:
Commercial Buildings	Tools	Easy-To-Use
Farms	Ramps	Resists Oil
Manufacturing Plants	Marine Docks	Resists Gasoline
Municipalities	Steps	Improves Traction
Nursing Homes	Ladder Rungs	Yields a Rough Finish
Office Buildings	Walkways	Long Life Formula
Recreation Centers	Railings	Variety of Colors
Repair Shops	Diving Boards	Non-Clogging Nozzle
Ship Yards	Concrete	Set to Touch In 10 minutes.
Warehouses	Wood	
	Ceramic	
	Fiberglass Surfaces	

## GOOD GRIP SLIP RESISTANT COATING

### DIRECTIONS:

Shake can well before using and between applications.  
Spray parts or object.  
Dry Time: Set to Touch - 10 Minutes  
Tack Free- 30 Minutes  
Traffic Ready - Minimum Overnight Dry

### TECHNICAL DATA:

Flash Point: -19°C (-2°F)  
Boiling Point: -44°C (-47°F)  
Stability: Stable at Normal Temperatures  
Specific Gravity: Between 0.77 and 0.90  
Solids Content: 20.1%  
Ignition Temperature: 365°C (689°F)

### CONTACT INFORMATION

OFFICE:  
1-888-6PURITY (678-7489)  
FAX  
1-877-9PURITY (978-7489)  
ADDRESS:  
114 SOUTHFIELD PKWY  
SUITE 120  
FOREST PARK GA. 30297  
[www.puritychemicals.com](http://www.puritychemicals.com)



# MSDS (material safety data sheet)

**PURITY CHEMICALS INC.**

114 Southfield Pkwy, Suite 120

Forest Park, GA 30297

Phone: 404-363-0767

Emergency Phone: 800-535-5053

## HMIS Rating:

Health 1

Flammability 4

Reactivity 3

Protection

0=Minimal

1=Slight

1=Moderate

3=Serious

4=Sever

Product Name: Good Grip Clear

Chemical Family:

**Section 1: Hazardous Ingredients**

Acetone, Propane, Xylene, Methyl isobutyl ketone, ethyl benzene, PM acetate

**Section 2: Physical Data**

Density: 519.6

Boiling Point: Negative 44°C

pH:

Appearance: Clear

Water Solubility:

Odor: Solvent

**Section 3: Fire and Explosion**

Flash Point: Negative 19°C

Extinguish Media: CO2, sand, extinguishing powder, or water spray.

Special Procedures:

None

Unusual Hazards: None Known

**Section 4: Reactivity Data**

Chemical Stability: Stable

Polymerization: N/A

Incompatibility: None Known

Decomposition: N/A

**Section 5: Health Information**

Toxicity: Harmful

Carcinogenicity: Classified as human carcinogen based on sufficient evidence.

Exposure Limit: Overexposure may cause permanent brain and nervous system damage.

Safety Precautions:

Wear protective equipment. Keep unprotected persons away.

**Section 6: Employee Protection**

Engineering Controls:

Keep away from foodstuffs and animal feed. Wash hands after use.

Eye Protection: Tightly sealed goggles

Skin Protection: Protective gloves. The glove material has to be impermeable and resistant to the substance.

Other:

**Section 7: First Aid**

Inhalation:

Supply fresh air. If necessary, provide artificial respiration. Keep patient warm.

Skin Contact: Remove contaminated clothing. Wash exposed area with soap and water.

Eye Contact: Move to fresh air. Rinse opened eye for several minutes under running water.

Ingestion: Contact physician or poison control center.

**Section 8: Disposal Information**

Spill, Leak or Release: Soak up spills with inert absorbent materials.

Waste Disposal: Dispose of in accordance with local, state, and federal regulations.

**Section 9: Storage**

Use only receptacles specifically permitted for this substance/product

**Section 10: Transportation**

DOT Proper Shipping Name: Not regulated

DOT/IMO Proper Shipping Name: Not regulated

The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for use, or any other warranty is expressed or is to be implied regarding the accuracy or the safety of this product, or the hazards related to its use. The information and the product are furnished on the condition that the person receiving them shall make his, or her, own determination as to suitability of the product for his, or her, particular purpose and on the condition that he or she assume the risk of his, or her, use thereof.