


# NATRA LUBE

## ORGANIC PENETRATING OIL

**NATRA LUBE** contains no silicones or harsh solvents, which can affect plastics, lacquers, insulation and paint. **NATRA LUBE** is forceful spray and powerful capillary action provides rapid penetration through rust and corrosion to free frozen parts. **NATRA LUBE** has a never-dry oil film that lubricates parts, reducing friction and wear, to ensure free and easy movement over a broad temperature range.



### FOR USE BY:

Airports  
Apartment Buildings  
Buildings Maint.  
Grounds Maint.  
Bus Lines  
Corrections  
Daycares  
Hospitals  
Hotels/Motels  
Medical Buildings  
Military  
Nursing Homes  
Packaging Plants  
Parks and Rec.  
Processing Plants  
Restaurants  
Sanitation Dept.  
Schools  
Street Departments  
WWTP

### FOR USE ON:

Frozen Nuts/Bolts  
Hinges  
Screws  
Clamps  
Linkages  
Fasteners  
Molds  
Lug Nuts  
Threaded Parts  
Tools  
Engine Parts  
Motors  
Bearings  
Gears

### FEATURE-BENEFIT:

Contains no silicones or harsh solvents that can harm plastics, lacquers, insulation or paint.  
Forceful spray helps blast through rust and corrosion  
Powerful capillary action rapidly climbs threads and penetrates into tiny voids to carry lubricant to where its needed.  
Long-lasting, never-dry oil film provides excellent lubricity over a broad temperature range.

## NATRA LUBE ORGANIC PENETRATING OIL

### DIRECTIONS:

Saturate part to be loosened and allow product to penetrate for a moment before attempting to break free. For heavily encrusted pieces a wire brush may be used to help remove corrosion. Apply a final spray to all parts prior to reassembly.

### TECHNICAL DATA:

Boiling Point: >300° F  
pH: N/A  
Appearance: Clear, light amber liquid  
Odor: Faint citrus odor  
Specific Gravity: 0.87  
Solubility in Water: Insoluble

### CONTACT INFORMATION

OFFICE:  
1-888-6PURITY (678-7489)  
FAX  
1-877-9PURITY (978-7489)  
ADDRESS:  
114 SOUTHFIELD PKWY  
SUITE 120  
FOREST PARK GA. 30297  
[www.puritychemicals.com](http://www.puritychemicals.com)



**MATERIAL SAFETY DATA SHEET**  
 COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

**SECTION I · PRODUCT IDENTIFICATION**

**Product Name:** Good Earth - Natra Lube Organic Penetrating Oil  
**Product Number:** \_\_\_\_\_ **Date Prepared:** 10/9/2007  
**Product Type:** AEROSOL  
**Formula:** Proprietary  
**Supplier's Name:** Purity Chemicals, Inc. **Information Phone:** (404) 363-0767  
**Supplier's Address:** P.O. Box 188, Forest Park, GA 30297 **Emergency Phone:** (800) 535-5053  
**DOT Ship Description:** Consumer Commodity, ORM-D

**HMIS Rating (Based on Aerosol Conc.):**  
 0-Minimal 1-Slight 2-Moderate  
 3-Serious 4-Extreme

<b>HEALTH:</b>	1
<b>FLAMMABILITY:</b>	2
<b>PHYSICAL HAZARD:</b>	0
<b>Personal Protection:</b>	B

**SECTION II · INGREDIENTS**

<b>CHEMICAL NAME</b>	<b>CAS #</b>	<b>%WT</b>	<b>313/Chem</b>	<b>Skin</b>	<b>Carcinogen</b>	<b>PEL</b>	<b>TLV-TWA</b>
Soybean Oil	8001-22-7	20 - 30	NO	NO	NO	15 mg/m3 (mist)	N/E
Citrus Terpene	5989-27-5	1 - 5	NO	NO	NO	N/E	N/E
Carbon Dioxide	124-38-9	1 - 5	NO	NO	NO	5000 ppm	5000 ppm

**SECTION III · PHYSICAL DATA**

**Aerosol Concentrate:**  
**Boiling Point:** >300°F **Specific Gravity (H2O=1)@70°F:** 0.87  
**pH:** N/A **Solubility In Water:** Insoluble  
**Appearance/Odor:** Clear, light amber liquid with faint citrus odor **Vapor Density(Air=1):** >1

**Total Contents:**  
**Total VOC %:** 5.85% **Vapor Pressure (can; psig @72°F):** 90 psi

**SECTION IV · FIRE AND EXPLOSION DATA**

**Flash Point (Conc.):** 125°F (TCC) **Flammability (as per CSMA Flame Projection Test):** Flammable Spray  
**Extinguishing Media:** Foam, CO2, Dry Media  
**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.  
**Unusual Fire and Explosion Hazards:** Exposure to temperature above 120° F may cause bursting.

**SECTION V · REACTIVITY DATA**

**Stability:** Material Stable. **Hazardous Polymerization:** Will not Occur.  
**Incompatibility:** Avoid contact with strong oxidizing agents.  
**Hazardous Decomposition Products:** Carbon Dioxide, Carbon Monoxide

**SECTION VI · STORAGE AND HANDLING**

**KEEP OUT OF REACH OF CHILDREN.** **NFPA Code 30B Rating:** Level 3 Aerosol.  
 For Industrial and Institutional use only.  
 Store in a cool, dry area away from heat or open flame.  
 Do not store at temperatures above 120° F.

**SECTION VII · HEALTH AND FIRST AID**

**PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:**

**Eyes:** May cause moderate irritation.  
**Skin:** Frequent or prolonged contact may cause irritation, drying and defatting of skin, and dermatitis. May aggravate existing skin conditions.  
**Inhalation:** Inhalation of mist can cause irritation of nasal and respiratory passages. Frequent or prolonged exposure may cause irritation to the upper respiratory tract, coughing, dizziness, nausea and headache.  
**Ingestion:** Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause lung injury.

**FIRST AID PROCEDURES:**

**Eyes:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.  
**Skin:** Wash with soap and water. If irritation persists seek medical attention.  
**Inhalation:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.  
**Ingestion:** Do not induce vomiting. Seek medical attention immediately.

**SECTION VIII · SPECIAL PROTECTION DATA**

**Respiratory Protection:** None needed for proper use in accordance with label directions.  
**Ventilation:** Provide local exhaust to keep concentration of Section II ingredients below acceptable limits.  
**Protective Gloves:** Use chemical resistant gloves if hand contact will be made.  
**Eye Protection:** Always wear safety glasses or chemical proof goggles when working with chemicals.

**SECTION IX · SPILL OR LEAK PROTECTION**

**STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:** Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

**WASTE DISPOSAL METHOD:** Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

**NOTICE:** The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.