

LIKE A ROCK

HARD SURFACE FINISH

LIKE A ROCK is a hard, durable, polish formulated with high gloss silicone and hard shiny wax. Dusts and adds glowing beauty, protection and shine to many hard surfaces. **LIKE A ROCK** helps remove dirt, dust, grime, fingerprints, ink and more. It leaves surfaces treated with a hard wax, moisture-resistant shield that protects against marking and spills. Treated surfaces also repel many graffiti marks made with pen, marker, paint, lipstick, etc. **LIKE A ROCK** dusts, polishes, and protects in one application. Helps reduce urine splash corrosion on metal lavatory partitions.



FOR USE BY:

Bars/Lounges
Cemetery
D.O.T.
Grounds Maint.
Highway Dept.
Hotels/Motels
Landscape Industry
Office Buildings
Parks and Rec.
Restaurants
Schools

FOR USE ON:

Lacquered Surface
Varnished Surface
Urethane Finishes
Plastic
Metal
Wood
Formica
Polished Stone
Linoleum
Porcelain
Vinyl
Baked Enamel

FEATURE-BENEFIT:

Safe on Plastic
Resists Marking
Buff in Seconds
Moisture-Resistant
Protects Against Spills
Easy to Apply
Economical
Reduces Metal
Lavatory Corrosion

DIRECTIONS:

Shake well before using. Hold can upright and spray surface to be protected from a distance of 12 to 14 inches. Do not wet excessively or overspray. Apply sparingly and evenly. Allow a moment for solvent to evaporate and wax haze to form shield. Buff lightly with a soft, dry cloth. Protect floors from overspray to prevent slippery conditions.

TECHNICAL DATA:

TYPE: Aerosol
Appearance: Clear
Odor: Lemon Scent
Solubility in Water: Slight
pH: N/A
Boiling Point of Concentrate: ~160°F
Propellant: Liquefied Petroleum Gas

LIKE A ROCK HARD SURFACE FINISH

CONTACT INFORMATION

OFFICE:
1-888-6PURITY (678-7489)
FAX
1-877-9PURITY (978-7489)
ADDRESS:
114 SOUTHFIELD PKWY
SUITE 120
FOREST PARK GA. 30297
www.puritychemicals.com

MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)



SECTION I · PRODUCT IDENTIFICATION

Product Name: LIKE A ROCK – HARD SURFACE FINISH Formula: Proprietary HMIS Rating (Based on Aerosol Conc.):
Product Number: 16211 Date Prepared: 04/30/04 0-Minimal 1- Slight 2- Moderate
Product Type: AEROSOL Emergency Phone: (800) 255-3924 3- Serious 4- Extreme
Supplier's Name: Purity Chemicals, Inc. Information Phone: (404) 363-0767 HEALTH: 2 FIRE: 4 REACTIVITY: 0
Supplier's Address: 114 Southfield Pkwy, Ste. 120, Forest Park, GA 30297 Personal Protection: B
D.O.T. Hazard Class: CONSUMER COMMODITY · ORM-D

SECTION II · INGREDIENTS

CHEMICAL NAME CAS # %WT 313/Chem Skin Carcinogen PEL TWA/TLV
Hexane 110-54-3 30-50 YES NO NO 400 ppm 400 ppm
Aliphatic Petroleum Distillates 64742-89-8 10-20 NO NO NO 300 ppm 300 ppm
Polydimethylsiloxane 63148-62-9 01-05 NO NO NO N/E N/E
Liquified Petroleum Gas 68476-85-7 40-60 NO NO NO 1000 ppm 1000 ppm

SECTION III · PHYSICAL DATA

Data Below Based On Aerosol Concentrate Only:
Boiling Point: ~160° F
pH: N/A Vapor Density(Air=1): >1
Solubility In Water: Slight Specific Gravity (H₂O=1)@75°F: 0.701
Appearance/Odor: Clear Yellow Liquid, Lemon Scent
Data Below Based On Total Contents:
Vapor Pressure of can (psig @70°F): 50
Total VOC (Volatile Organic Compounds)%: ~95%

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (of Concentrate Only): 0°F (T.O.C.) Flammability (as per USA Flame Projection Test): Extremely-Flammable Spray
Extinguishing Media: Foam, CO₂, Dry Media
Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.
Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.

SECTION V · REACTIVITY DATA

Stability: Material Stable. Hazardous Polymerization: Will not Occur.
Incompatibility: Avoid contact with strong oxidizing agents.
Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxides.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.
For Industrial and Institutional use only.
Store in a cool, dry area away from heat or open flame.
Do not store at temperatures above 120° F. NFPA Code 30B Rating: Level 3 Aerosol.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:
Eyes: May cause slight irritation but does not injure eye tissue.
Skin: Frequent or prolonged contact may cause irritation.
Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis..

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.
Skin: Wash with soap and water. If irritation persists seek medical attention.
Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.
Ventilation: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.
Protective Gloves: None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.
Eye Protection: None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.