


WAX STRIP

BASEBOARD CLEANER & WAX STRIPPER

WAX STRIP quickly removes soil, wax and most Copolymer finishes that build up on baseboards, in corners or in other hard to reach areas. WAX STRIP will not harm painted surfaces. Fortified with citrus terpenes to boost cleaning ability and mask necessary caustic additives. Inverted spray valve enable easy application from waist height.



FOR USE BY:

Airports
Grocery Stores
Hospitals
Janitorial Services
Nursing Homes
Office Buildings
Public Restrooms
School Systems
Sports Facilities

FOR USE ON:

Baseboards
Corners
Edges
Steps
Under Cabinets
Tiles
Porcelain
Around & Behind
Urinals

FEATURE-BENEFIT:

Clings to Vertical Surfaces

Removes Wax Build-Up from Hard to Reach Areas
Nor Harsh or Foul Chemical Odors
Non-Flammable
Pleasant Aroma

DIRECTIONS:

Use in Upside Down Position Only. Spray holding can approximately 6 to 10 inches from baseboard or surface to be cleaned. Apply in a thin, even coating that covers the soil & wax. Allow to remain on surface for 3 to 5 minutes. Wipe away residue with wet sponge. For stubborn films rub the area with a wet scrub pad and then sponge away residue.

NOTE: May dull some painted surfaces if allowed to set.

TECHNICAL DATA:

Appearance and Odor: Opaque White Liquid
Flash Point of Concentrate: 187°F
Flammability: 120°F
Specific Gravity: 75°F: 1.009
Propellant: H2O-1
Spray Pattern: Circular

WAX STRIP BASEBOARD CLEANER & WAX STRIPPER

CONTACT INFORMATION

OFFICE:
1-888-6PURITY (678-7489)
FAX
1-877-9PURITY (978-7489)
ADDRESS:
114 SOUTHFIELD PKWY
SUITE 120
FOREST PARK GA. 30297
www.puritychemicals.com



MATERIAL SAFETY DATA SHEET
COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION

Product Name: Wax Strip
Product Number: 178
Product Type: AEROSOL
Formula: Proprietary
Supplier's Name: Purity Chemicals, Inc.
Supplier's Address: P.O. Box 188 Forrest Park, GA30297
DOT Ship Description: CONSUMER COMMODITY, ORM-D

Date Prepared: 11/15/2007
Information Phone: (404) 363-0767
Emergenc Phone: (800) 535-5053

HMIS Rating (Based on Aerosol Conc.):
 0-Minimal 1-Slight 2-Moderate
 3-Serious 4-Extreme

HEALTH:	2
FLAMMABILITY:	2
PHYSICAL HAZARD:	1
Personal Protection:	B

SECTION II · INGREDIENTS

CHEMICAL NAME	CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TWA/TLV
Ethylene Glycol Monobutyl Ether	111-76-2	1 - 10	YES	YES	NO	50 ppm	20 ppm
Isoparaffinic Hydrocarbon	64741-66-8	1 - 10	NO	NO	NO	N/E	281 ppm*
Citrus Terpene	5989-27-5	1 - 10	NO	NO	NO	N/E	N/E
Liquefied Petroleum Gas	68476-86-8	15 - 25	NO	NO	NO	1000 ppm	1000 ppm

* Manufacturer's recommended exposure limit (TWA).

SECTION III · PHYSICAL DATA

Aerosol Concentrate:
Boiling Point: ~207°F **Specific Gravity (H₂O=1) @70°F:** 0.99
pH: 12.8 **Solubility In Water:** Complete
Appearance/Odor: Opaque, white liquid with ammoniated/citrus odor **Vapor Density(Air=1):** >1

Total Contents:
Total VOC %: 30.41% **Vapor Pressure (can; psig @72°F):** 55 psig

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (Conc.): 187°F **Flammability (as per CSMA Flame Projection Test):** Non-Flammable Spray
Extinguishing Media: Foam, CO₂, Dry Media
Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.
Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.

SECTION V · REACTIVITY DATA

Stability: Material Stable. **Hazardous Polymerization:** Will not Occur.
Incompatibility: Avoid contact with strong oxidizing agents.
Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN. **NFPA Code 30B Rating:** Level 1 Aerosol.
 For Industrial and Institutional use only.
 Store in a cool, dry area away from heat or open flame.
 Do not store at temperatures above 120° F.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:
Eyes: Causes severe irritation, redness, tearing and blurred vision. May aggravate existing eye conditions.
Skin: Prolonged contact causes irritation, redness and possible burns. May aggravate existing skin conditions.
Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages and damage to mucous membranes. May aggravate existing respiratory conditions. Prolonged or repeated inhalation may cause headaches, dizziness, drowsiness, and unconsciousness. Abusive overexposure may cause mild, reversible kidney and liver effects, blood abnormalities and other central nervous system effects, including death.
Ingestion: Can cause severe irritation and damage to mucous membranes and deep tissue. Aspiration of the material into the lungs could cause severe pulmonary injury, possibly progressing to death.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.
Skin: Wash affected area with soap and water. If irritation persists seek medical attention.
Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
Ingestion: Do not induce vomiting. Rinse mouth with water and then drink one glass of water. Never give anything by mouth to an unconscious person. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.
Ventilation: Provide local exhaust to keep air concentrations of ingredients listed in Section II below acceptable limits.
Protective Gloves: Wear chemical resistant gloves.
Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.
WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.