

ZENWAX POLISH

WAX & SHINE

ZENWAX POLISH is a quick and easy to use wax and shine that restores color and shine to automotive finishes. Formulated with special micro refined clays and synthetic wax to provide the ultimate shine. **ZENWAX POLISH** is a aerosol wax that sprays on and buffs effortlessly to create a hard shell finish. **ZENWAX POLISH** is an excellent wax and polish for anything that needs reviving, also maintains the beautiful factory original shine.



FOR USE BY:	FOR USE ON:	FEATURE-BENEFIT:
Ambulances	Paint	Removes Oxidation
Mechanics	Plastic	Restores Brilliance
Bus Lines	Rubber	Aerosol Wax
Cab Companies	Chrome	Creates Hard Shell Finish
D.O.T.	Gel Coat	
Delivery Services	Fiberglass	
Detail Shops		
Fire Departments		
Florists		
Marinas		
Parcel Companies		
Police Departments		
Schools		
Trucking Companies		

DIRECTIONS:

Product should be warmed to room temperature. Move vehicle out of direct sunlight if possible. Shake well before using, Wash first to remove excess dirt, Spray and lightly wipe over surface, Buff with clean, dry cloth to a high luster.

TECHNICAL DATA:


Appearance:
Boiling Point: <0 to 5720 F
Specific Gravity (H2O=1)
Solubility in Water: Emulsifiable
Flash Point: Propellant <00F

ZENWAX POLISH WAX & SHINE

CONTACT INFORMATION

OFFICE:
1-888-6PURITY (678-7489)
FAX
1-877-9PURITY (978-7489)
ADDRESS:
114 SOUTHFIELD PKWY
SUITE 120
FOREST PARK GA. 30297
www.puritychemicals.com

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration
MATERIAL SAFETY DATA SHEET
(Prepared According to 29 CFR 1910.1200)



SECTION 1 IDENTIFICATION
Product Name: **FORMULA 494755 ZENWAX**
Manufacturer's Name: ZENEX International
Manufacturer's Address: 7777 First Place, Cleveland Ohio 441146
Manufacturer's Phone Number: (440) 232-4155
Emergency Phone Number: 1-800-535-5053
Proper Shipping Name: Consumer Commodity, ORM-D
Effective Date: 4-15-02

SECTION 2 IDENTIFY INFORMATION AND HAZARDOUS INGREDIENTS

Chemical Name: CAS No.: TLV:
Water 7732-18-5 Not applicable
Propane 74-98-6 2500ppm
Isobutane 75-28-5 Not established
n-Butane 106-97-8 800ppm
Kerosene 8008-20-6 Not available
Mineral Spirits 8052-41-3 100ppm
Kaolin Clay 66402-68-4 2 mg/m³ as dust
Silicone 63148-62-9 Not established

SECTION 3 PHYSICAL DATA

Boiling Point: <0 to 5720 F Specific Gravity(H₂O=1): 0.90 + 0.05
Solubility in Water: Emulsifiable Evaporation Rate: Slower than Ether
Vapor Density(Air=1): Heavier than air

SECTION 4 FIRE AND EXPLOSION HAZARD DATA

Flash Point (Propellant): <00F
Flammable Limits (Propellant): LEL: 1.0 UEL: 9.5
Extinguishing Media: Use water fog; dry chemical or carbon dioxide.
Special Fire Fighting Procedures: Aerosol cans may rupture when heated.
Unusual Fire and Explosion Hazards: Heated cans may burst.

SECTION 5 REACTIVITY DATA

Stability: Unstable _____
Stable X
Incompatibility (Materials to Avoid): None known.
Conditions to Avoid: High temperatures.
Hazardous Decomposition or Byproducts: In fire, will decompose to carbon dioxide, carbon monoxide, silicon dioxide.
Hazardous Polymerization: Will not occur

SECTION 6 STORAGE AND HANDLING INFORMATION

Precautions to be Taken in Handling and Storing:
When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.
STORE AT TEMPERATURES BELOW 120oF KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME KEEP AWAY FROM CHILDREN FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY FOR USE BY TRAINED PERSONNEL ONLY
KEEP CONTAINER CLOSED DURING STORAGE

SECTION 7 HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
SKIN: Skin irritant. Will cause detaching of skin. Effects are reversible.
EYES: Eye irritant. Will cause redness and burning sensation.
INHALATION: Effects of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death. INGESTION: Aspiration hazard if swallowed.
First Aid Procedures: SKIN: Immediately flush exposed area with water for at least 15 minutes. If irritation persists, get medical attention. Remove contaminated clothing and launder before reuse. EYES: Immediately flush with large quantities of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Seek medical attention. INHALATION: Remove person to fresh air. If irritation persists, give oxygen, get medical attention. INGESTION: DO NOT induce vomiting. Seek medical attention immediately. Note: Never give anything by mouth to an unconscious or convulsing victim.
Keep person warm and quiet.

SECTION 8 SPECIAL PROTECTION INFORMATION

Respiratory Protection: Self-contained breathing apparatus if above TLV limit.
Ventilation: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: None required if spraying.
Eye Protection: As with all cleaners, ZENEX supports employee safety as priority #1. Therefore, we recommend the use of safety glasses or chemical splash goggles. Other Protective Equipment: Long sleeves and long pants.
Work/Hygenic Practices: Do not smoke while using. Wash hands after use.

SECTION 9 SPILL OR LEAK PROCEDURE

Steps To Be Taken In Case Material Is Released or Spilled:
Use absorbent sweeping compound to soak up material. Put into container. Dispose as hazardous waste. Waste Disposal Method: Dispose as hazardous waste in accordance with EPA RCRA.

SECTION 10 REGULATORY INFORMATION

SARA Title III, Section 313 Components: None
This information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition. We make no warranties, express or implied, and assume no liability in connection with any use of this information. 494755