

ZENASHINE PLUS

DETAIL SPRAY

ZENASHINE PLUS detail spray is an economical alternative to higher priced dressings. **ZENASHINE PLUS** is fast and easy to use while enhancing the appearance of rubber, vinyl, and leather. The fine aerosol mist is ideal for those hard-to-reach vents and textured surfaces. No wiping necessary. **ZENASHINE PLUS** promotes and increases the life of rubber surfaces. It works instantly and leaves behind a fresh watermelon scent.



FOR USE BY:	FOR USE ON:	FEATURE-BENEFIT:
Ambulances	Vinyl	Fast Drying
Cab Companies	Rubber	Non- Greasy
D.O.T.	Tires	No Wiping Necessary
Delivery Services	Dashboards	Economical
Detail Shops	Exterior Trim	Easy To Use
Fire Departments	Window Trim	Water Resistant
Florists	Vents	High Gloss
Parcel Companies	Wheels Covers	Watermelon Scent
Police Departments	Bumpers	Works Instantly
Schools	Door Seals	Excellent for hard-to-reach- areas
Trucking Companies	Bumper Trim	

ZENASHINE PLUS DETAIL SPRAY

DIRECTIONS:

Shake well before using. Prepare surface by removing dirt, dust, oil, and grease. Dry surface. Test spray on an inconspicuous area or scrap piece to check compatibility. Hold can 10" to 12" from surface. Use a stroking motion. Apply two or more coats rather than one heavy coat. For best results, spray at 70°F to 80°F. Polish surface, if desired, using a soft cloth after allowing spray to dry a few minutes.

TECHNICAL DATA:

Type: Aerosol Dressing
Conditions to Avoid: High Temperatures
Specific Gravity (H2O-1) @ 70° F: 0.70 ± 0.05
Boiling Point: <0 to 610° F
Flash Point: <0° F
Water Solubility: Nil
Storage Stability: Stable

CONTACT INFORMATION

OFFICE:
1-888-6PURITY (678-7489)
FAX
1-877-9PURITY (978-7489)
ADDRESS:
114 SOUTHFIELD PKWY
SUITE 120
FOREST PARK GA. 30297
www.puritychemicals.com

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration
MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910.1200)



SECTION 1 IDENTIFICATION

Product Name: **FORMULA 44736 ZEMASHINE PLUS**
 Distributor's Name: **Purity Chemicals**
 Distributor's Address: **114 Soutter Drive, Suite 120, Forest Park, GA 30027**
 Distributor's Phone Number: **(404) 353-0757**
 Emergency Phone Number: **1-800-876-9263**
 Proper Shipping Name: **Consumer Commodity, OSHA**
 Effective Date: **09-15-01**

SECTION 2 IDENTIFY INFORMATION AND HAZARDOUS INGREDIENTS

Chemical Name:	OSHA No.:	TLV:
Hexane	110-54-9	50ppm
Propene	74-98-6	2500ppm
Isobutane	75-98-5	Notationed
n-Butane	106-97-8	800ppm
Stilbene	63149-82-0	Not available
Unrefined Oil	8042-47-5	5 mg/m ³ as mist

SECTION 3 PHYSICAL DATA

Boiling Point:	<10 to 810°F	Specific Gravity (H ₂ O=1):	0.70-0.06
Solubility in Water:	Nil	Vaporization Rate:	Slower than Ether
Vapor Density (Air=1):	Heavier than air	pH:	NA

SECTION 4 FIRE AND EXPLOSION HAZARD DATA

Flash Point:	<0°F
Formaldehyde:	LEL: 1.8 UEL: 9.5
Extinguishing Media:	Use water fog dry chemical or carbon dioxide.
Special Fire Fighting Procedures:	Aerosol cans may rupture when heated.
Unusual Fire and Explosion Hazards:	Heated cans may burst.

SECTION 5 REACTIVITY DATA

Stability: Unstable
 Incompatibility (Water, acids, alkalis): Stable
 Oxidation Potential: None known
 Hazardous Decomposition Products: None, will decompose to carbon dioxide, carbon monoxide, silicon dioxide.
 Hazardous Polymerization: Will not occur

SECTION 6 STORAGE AND HANDLING INFORMATION

Precautions to be Taken in Handling and Storage:
 When spraying more than one half can consecutively, use MOSH approved respirator.
STORE AT TEMPERATURES BELOW 130°F
KEEP AWAY FROM CHILDREN
FOR USE BY TRAINED PERSONNEL ONLY

KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY
KEEP CONTAINER CLOSED DURING STORAGE

SECTION 7 HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
 SKIN: Skin irritant. Will cause drying of skin. Effects are reversible.
 EYES: Eye irritant. Will cause redness and burning sensation.
 INHALATION: Effects of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death.
 INGESTION: Aspiration hazard if swallowed.

Prolonged and repeated overexposure to hexane may cause damage to nerve tissue of the arms and legs (peripheral neuropathy), resulting in muscular weakness and loss of sensation. Repeated and prolonged overexposure to solvents may cause permanent brain and nervous system damage.

First Aid Procedures:

SKIN: Immediately flush exposed area with water for at least 15 minutes. If irritation persists, get medical attention. Remove contaminated clothing and launder before reuse.
 EYES: Immediately flush with large quantities of water for at least 15 minutes. Lift upper and lower eyelids occasionally. Seek medical attention.
 INHALATION: Remove person to fresh air. If irritation persists, give oxygen, get medical attention.
 DO NOT induce vomiting. Seek medical attention immediately.
 Note: Never give anything by mouth to an unconscious or comatose victim. Keep person warm and quiet.

SECTION 8 SPECIAL PROTECTION INFORMATION

Respiratory Protection: Self-contained breathing apparatus if above TLV limit.
 Ventilation: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.
 Protective Gloves: None required if spraying.
 Eye Protection: As with all cleaners, PURITY supports employee safety as priority #1. Therefore, we recommend the use of safety glasses or chemical splash goggles.
 Other Protective Equipment: Long sleeves and long pants.
 Work/Hygiene Practices: Do not smoke while using. Wash hands after use.

SECTION 9 SPILL OR LEAK PROCEDURE

Steps To Be Taken in Case Material is Released or Spilled:
 Use absorbent sweeping compound to soak up material. Put into container. Dispose as hazardous waste.
 Waste Disposal Method:
 Dispose as hazardous waste in accordance with EPA RCRA.

SECTION 10 REGULATORY INFORMATION

SAHA Title III, Section 318 Components:
 Hexane 110-54-9

This information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition. We make no warranties, express or implied, and assume no liability in connection with any use of this information.

494785